


TILLEY FIBERGRATE



TILLEY FIBERGRATE

PRODUCT INFORMATION

Combining unmatched corrosion resistance with strength, long life and safety, Tilley Fibergrate Composite Structures sets the standard for fiberglass reinforced plastic (FRP) molded products. Fibergrate products are proven to deliver years of reliable service, even in the most demanding corrosive conditions - conditions which cause conventional metallic and wood products to deteriorate rapidly.

Fibergrate molded gratings are available in a variety of resins, standard and custom colours, depths, panel sizes and mesh configurations. Surface options include an integrally applied grit coating that provides superior slip resistant footing in most environments including wet or oily conditions and is the standard surface for most Fibergrate molded gratings. A meniscus top with a concave surface grating is also available on request.


Fibergrate molded grating is used in place of traditional materials for a FRP solution that fits a wide range of applications and environments. Load tables available on request.

Type	Depth mm	Mesh mm	Standard panel sizes mm	Weight per M2	Open area
Tilley Fibergrate	38	38 x 38 Square	3660 x 1220 and 1830 x 1220	18.6 kg	70%





38MM DEEP x 38MM SQUARE MESH

# of Bars/m of width	Load bar width	Open area	Load bar centres	Approximate weight
26	6.4mm	70%	38mm	18.6 kg/m ²

PLAN VIEW



ELEVATION VIEW



WELLINGTON

1-7 Jean Batten St, Rongotai,
Wellington 6022, New Zealand

T +64 4 387 7009 E wgtnsales@tilleyandpatton.co.nz

AUCKLAND

36 Aranui Rd, Mt Wellington,
Auckland 1060, New Zealand

T +64 9 527 7385 E akldsales@tilleyandpatton.co.nz

CHRISTCHURCH

Level 1/306 Port Hills Rd, Hillsborough,
Christchurch 8022, New Zealand

T +64 3 331 6565 E chchsales@tilleyandpatton.co.nz

SPECIALISTS IN THE DESIGN AND MANUFACTURE
OF SHEET METAL COMPONENTS AND PRODUCTS